



2023 HELI Global Distributor Conference

www.heliforklift.net

HELI

WITH HELI, SHAPING
A SMARTER FUTURE

H SERIES

2.0-3.0 t

Electric Pallet Truck



- Small turning radius is more suitable for working in narrow spaces.
- The truck has excellent climbing performance and wide operating occasions.
- The truck adopts dynamic driving wheel load boosting mechanism for better driving performance.
- Adjustable height of folding arm guard suits for passengers of different heights and operation habits.
- The folding station board has better shock absorption effect and more comfortable driving experience through the combined action of shock absorption springs and cushions.
- Adopting ZAPI AC drive controller and ZF gearbox, the overall performance of the pallet is more reliable.



COMFORT AND
ENERGY SAVING



STABLE AND
RELIABLE



INTELLIGENT
SECURITY



CONVENIENT
MAINTENANCE

2.0-3.0 t

H SERIES

Electric Pallet Truck

Technical Data

| Characteristics | | |
|--|------|-------------------------------|
| Model | | CBD30-A2RLiH |
| Rated capacity | kg | 3000 |
| Load center | mm | 600 |
| Operating type | | Stand on/Pedestrian propelled |
| Wheels type | | PU |
| Max.Fork lifting height | mm | 122 |
| Outside width between forks | mm | 560 |
| Fork length/width/thickness | mm | 1150x170x55 |
| Overall length | mm | 1822/2235 |
| Overall width | mm | 760 |
| Overall height(with handle) | mm | 1404 |
| Min.Turning radius | mm | 1590 |
| Min.Aisle width for right angle stacking (for pallets 800x1200) | mm | 2153 |
| Min.Aisle width for right angle stacking (for pallets 1000x1200) | mm | 2240 |
| Max.Travelling speed(loaded/unloaded) | km/h | 8/12.5 |
| Max.Gradeability(loaded/unloaded) | % | 6.5/25 |
| Battery voltage/rated capacity | V/Ah | 24/270 |
| Drive motor/lift motor | kW | 2.8/2.2 |
| Controller | | ZAPI |
| Battery weight | kg | 130 |
| Service weight with battery | kg | 660 |



ANHUI HELI CO., LTD.

Add / No.668, FangXing Road, Hefei, China

Fax / +86-551-63639966

Tel / +86-551-63639068(America); 63639258(Europe);
63639358(Asia); 63662105(Africa & Middle East)

* Our products are subject to improvements and changes without notice.



LinkedIn



YouTube



Facebook